







- 清廢機護蓋,除了有確保操作人員安全的作用外,更能防止爪鏈損壞紙盒邊料 以及維持紙盒之排列整齊。
- 利用高速氣動馬達傳動爪鏈,取代傳統人力槌擊清廢。
- 能於短時間內完成去除軋盒邊料之效果,每秒約可清除400張成疊之盒型邊料。
- High speed rotating studded chain strips the sheets exterior trim.
- Cover protect device prevents damage to the sheets and arrange the sheets in regular. Ensure the safety for operator as well.
- Apply pneumatic motor to drives the chain with high speed to substitute for the manual.
- Removed the stack of 400 sheets high in one second, performing instant stripping result.



- 大幅降低人力去除廢料時間,確保盒型之品質及穩定性。
- 耐用之除屑齒爪,使用高剛性及高韌性之材料。
- 手提式省力設計,操作簡便。
- Lower the personal expense and time waste substantially. Ensure the carton quality and stability.
- Durable chain design with high hardness, strength and toughness.
- Portable design economize on labor expend and easy to operate.



Before



氣動清廢機 Carton Stripper

型 號 Model	WPA CS5
爪鏈數量 Number of chains	五 爪 式 5 rows
爪鏈寬度 Width of chains	20 mm
最大除屑範圍 Max. Stripping Range	除屑長度 250mm 以下可完整一次除屑 除屑長度 250 mm~ 450 mm 依盒型、紙厚而定 Sheets under 250mm length, present excellent stripping performance. Sheets between 250 to 450 mm long depend on the depth and shape of sheets.

搭配高速缺口機使用 能使除屑效能發揮淋漓盡致 Combine with Easynick Grinder Performing excellent strips



砂輪片建議規格 / Suggestions for nicks width up to $300g/m^2 = 0.5mm$ up to $600g/m^2 = 0.8mm$

技術資料

Technical parameter

適 用 紙 張 Material	紙 板、瓦 楞 紙 板 Cardboard and Corrugated Board	
爪 鏈 速 度 Rotating Chain Speed	MAX. 4.2 m/sec.	
空 壓 需 求 Air Supply Requirement	6 kg / cm ² (6 BAR)	
機 器 尺 寸 Dimension	230 (W) x 470 (L) x 210 (H) mm	
機 器 重 量 Net Weight	4 kg	

禾順機械股份有限公司 WIN PACK MACHINERY CO., LTD.





1152 Tourmaline Drive Newbury Park, CA 91320 Office: (805) 480-3300

www.matchmachinery.com